



Trademarks and disclaimers

IEEE believes the information in this publication is accurate as of its publication date; such information is subject to change without notice. IEEE is not responsible for any inadvertent errors.

Other tradenames and trademarks in this document are those of their respective owners.

The Institute of Electrical and Electronics Engineering, Inc. 3 Park Avenue, New York, NY, 10016-5997, USA

Copyright © 2000 by the Institute of Electrical and Electronics Engineers, Inc. All rights reserved. Published December 2000. Printed in the United States of America.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

To order IEEE Press publications, call 1-800-678-IEEE.

Print: ISBN 0-7381-2601-2

SP1122

See other standards and standards-related product listings at: http://standards.ieee.org/

The publisher believes that the information and guidance given in this work serve as an enhancement to users, all parties must rely upon their own skill and judgement when making use of it. The publisher does not assume any liability to anyone for any loss or damage caused by any error or omission in the work, whether such error or omission is the result of negligence or any other cause. Any and all such liability is disclaimed.

This work is published with the understanding that the IEEE is supplying information through this publication, not attempting to render engineering or other professional services. If such services are required, the assistance of an appropriate professional should be sought. The IEEE is not responsible for the statements and opinions advanced in this publication.

Library of Congress Cataloging-in-Publication Data

IEEE 100: the authoritative dictionary of IEEE standards terms.—7th ed.

p. cm.

ISBN 0-7381-2601-2 (paperback : alk. paper)

- 1. Electric engineering—Dictionaries, 2. Electronics—Dictionaries, 3. Computer engineering—Dictionaries, 4. Electric engineering—Acronyms, 5. Electronics—Acronyms.
- 6. Computer engineering—Acronyms. I. Institute of Electrical and Electronics Engineers.

TK9 .I28 2000 621.3'03—dc21

00-050601

Content

Introduction

How to Use

Categories

Trademark:

The Author

Abstracts a

Non-IEEE S

de generator.

which contains manually or meare to be subsequently punched

containing information that is to example, an original invoice, a (C) 610.10-1994w

machine-readable document. (C) 610.2-1987

s) The ratio of emitted optical supplies a piece of trace infor-(C/PA) 1224.1-1993w

ut electrical power.

g of a source, usually the signal nission system) Potential refer-(Std100) 812-1984w

of a source specification. (C/PA) 1387.2-1995

ak analysis; input impedance. pedance presented by a source of ds of a device, or network. See

(SP/IM/HFIM) 151-1965w, [40] on line and the status (i.e., opened ismission line. In network applit impedance of an electrical sysassociated with the transmission vary depending on the location (PE/PSR) C37.113-1999

mpedance stabilization networks st applications to test the UUT. rce impedance. Different LISNs mnects used in the system should es with each input line to provide s defined to begin at the power is included in the source impedat the power source return ter-(PEL) 1515-2000

on process is represented. For exwrite a computer program. Con-The language in which the input (C) 610.2-1987, 610.12-1990

nalysis) A node having only outbedance. (COM/TA) 661-1979r ed to be 900 Ω resistive. See also: impedance used for determining mess ratings of telephone con-(CAS) 155-1960w

contribute significant amounts of s within the duration of fault clearation to be connected to a terminal ed faults involving ground if they be a significat source of zero-set current. For instance, large synninal that contributes a significant on the protected line. Note that originates data. See also: desti-(C/BA) 1355-1995

ortion of a source specification (PE/PSR) C37.113-1999 (C/PA) 1387.2-1995

;-zag winding.

ded neutral connected to the line

source, radioactivity standard See: radioactivity standard source, radioactive See: radioactive source.

source resistance The resistance presented to the input of a device by the source. See also: measurement system.

source resistance rating The value of source resistance that resistance, will either double the dead band or shift the dead when injected in an external circuit having essentially zero band by one-half its width. See also: measurement system. (BEC/EMI) [112]

source role Where the software exists in a form suitable for removed by a task initiated by the manager. The source role pository of software from which the manager may choose to distribution, forming a context for the establishment of a reprovides a repository where software may be stored and prodistribute to targets. Software exists in the source until it is vides access for those roles that require the software. (C/PA) 1387.2-1995

source routing (1) A bridging technique where frames contain (3) The capability for a source to specify the path that a frame Within the source routed frame, the station specifies the route (2) A mechanism to route frames through a bridged LAN trame. Contrast: spanning tree. must know the route to the destination before sending the frame to reach the destination. In this scheme, the transmitter the list of bridges and networks that must be traversed for the will use to traverse the bridged network. that the frame will traverse. (C/LM) 8802-5-1998 (C) 610.7-1995

(C/LM/CC) 8802-2-1998

Source Routing Transparent (SRT) The bridging technology specify the path through the bridged network (source routing) the transparent bridging rules allowing the source station to defined by ISO/IEC 10038:1993, annex C, as an extension to (C/LM/CC) 8802-2-1998

source segment in a hierarchical database, a segment that contains the data used to construct a secondary index. (C) 610.5-1990w

source/sink device Source devices originate signals, whereas vices include channel banks and digital crossconnect systems. sink devices terminate signals. Examples of source/sink de-(COM/TA) 1007-1991r

source statements (SS) The encoded logic of the software prod (C/SE) 1045-1992

and power lines? Twenty imposed for ratio of the pressure of a set, expressed in decibels. The applicitly stated. Nature 1. The are in common use: 20 minus.

source (1) (beer maser) Taken to mean either juggid Jiberhaused reflecting surface. (JED) 386 (3) (meta-bailed-evalut field-effect fermatap) jug-the device sundance of an insulated-participal effection of the contract of an insulated-participal effection.

effective sound pressure.

source-to-line impedance ratio (SIR) The ratio of the source impedance behind a relay terminal to the line impedance. (PE/PSR) C37.113-1999

SP See: space character.

SPA See: scratchpad area.

space (1) (data transmission) One of the two possible condiacters and six unit intervals between words. Morse code, a duration of two unit intervals between chartions of an element (bit); an open line in a neutral circuit. In

> MTA) 169-1882. 1286-1996 Hothe base 10 of the ratio of 0 of the raise of the pressure

as the size of a single character. (D) (data management) One medium. (C) (data management) A basic unit of area such tended for the storage of data such as a location in a storage to a prescribed format. (B) (data management) A site incations, the "zero's" state. Contrast: mark. (2) (A) To advance the reading or display position according (3) The absence of a signal; for example, in data communior more space characters. (C) [20], 610.5-1990 (PE) 599-1985w

(C) 610.10-1994w

s de depailme to de los el 10 s' passed probe A, desies that esponde to Link (1900).

The effective point, (1911 98, passed son es la resultation de la consideration CPA 1984-1995

CPA 19 lowing standard willists: owt, be, ed, low, lood le-line, red, and year. Source code can also when so a fain i source meeting any or all of these meanings.

(PECEM) 85-1973w he logarithm to the base ton of w) to the reference power of capable to seeman plature plature of the capability of sound cellection coefficient (surface) The participation referred by the ordinate of the saund involve paging "linker observator perfect of the capability sound recording system A combination of the and associated equipment suitable for auxing capable of subsequent reproduction, See of

eard A data card which contains rearneally or ret-recorded data that are to be subsequently purched the card. (C) 610 30-1994w

sneed treet (electroscoustics) A band that a record, in some cases, a plumity of such his in mound film recording, the band is resurity eproducing system A combination of and associated equipment for replace ectrum analyzer (sound analyzer).

of mesoning the band pressure keel en desercial A document containing information that i graph is a computer. For example, an original invoke the plane out card, or a machine-readable thousand the plane out card, or a machine-readable thousand the containing the the MD that supplies a piece of trace into

(PE/TR) CST-12:90-1999 d See: A-weighted sound power

Remory (Siber apriles) The ratio of emitted optical (d) a number to the input electrical power.
(Statistic) 812-1954w ione (signal-tennémicsion system) Potential refer-ion physical location of a source, usually the signal the stor signal. (IE) [43]

The distribution of a source specification of the product of a source of CRAN 19872-1995 and the product of the distribution o

(PEFSR) C37.1
see impedance is defined to begin at the facultion and end at the power source referre, at eabling is included in the source.

e for different test applications 200

(4) A generatur of normal characters as 8 'Est, also 'Assemi characters. (2) B. (5) The questionation of severe destribution of write standardization willing. The counter has by on learns for source, sold as assembly past on learns for source, band, and the source (24) at this to the source band, and the source (24) at (6) A nocks that initiates a best treasfer. (25)

(C#4) 18

The tode that creates a send or echo patell is operationed in the third symbol of ov into change to ward the drain. It has the go is the surrective than the drain for the certain

minimized (software) The language in which in graph to which in gipplice-olded translation products it represents the product for the product of the state of the

source address (SA) (1) The address of a defact focusion from which data it to be transferred (Gas transferred address; declination.

(7) The start of a delay art; that is, that is signal. For arts across cell instances, the poping for area across interconnect, the court ping for area across interconnect, the court

The state of the s d lapedance (laudants ratings of religiones). The source/hand impedance used for determinating is considered to be 900 E-resisted. See impedance: load impedance. (COMFA) 661-17 insi podo which originates data. See also: desu-(C/BA) 1355-1995 (network analysis) A sock having only (CAS) 155-1

Spiriteling side a grounded service concentration on the line.

Spiriteling side as the service of the line.

Spiriteling spiriteline.

Spiriteline spiriteline spiriteline spiriteline spiriteline spiriteline.

source program (coffinate). A computer program that must be compiled, assembled, or otherwise translated in order to be executed by a computer. Contratt: object program. (C) 610.12-1990

power quench in neuvorking, a melhod for extentibility con-gestion in which a device descets the congestion and requests that the source step transmittings, for also, impressing, (C) 610.7-899) oures, radioactive See: radioactive conte

endioactivity standard Secr enforctivity standard

usee residence. The resistance executed to the input of a device by the course. See olso recommends system.

source resistance rating. The value of source resistance of when injected in an external circuit hardag occasionly resistance, will either should be feed that the first state of the contrast contrast the contrast that the first state of the contrast contrast years had by one half its width, for other interestorment by the hand by one half its width, for other interestorment of IEEE/ED(N).

when the When the individual state of the st

abarte souling (1) A régigie tréchaige whest farons cessain ha liet of bridges an évent farons cessain ha leis of bridges an évent des voix les transmitter france to mach the destination In this debates, the transmitter paul hours de result to the destination before acading to flores, Commett apassitel part, a mengh to NG 400 11 NS. When the estimate the form the destination appetite the row Will have resulted in terrets.

(CLM) the appetite (for a source to spreif) of publishes a form of will use to transmits the bridged retwork.

(S) The application of the source of spreifs of publishes a form of will use to transmits the bridged retwork.

Capland State (1978) Instructionary Selection (1980) Capland State (1980

nource expressi in a hierarchical deathers, a regment that contains the data used to construct a secondary index.
(C) 6(0,5-1990w

pource statements (SS) The encoded logic of uct. sourcestink device Source devices originate signals, sink devices terminate signals. Examples of source vices include charact banks and digital crosscapator vices include charact banks and digital crosscapator. (C/SE) 1045-1997

SP See: space character. SPA See: somichpad area. owner-to-line impedance ratio (SIR) The ratio of the source impedance behind a relay terminal to the line impedance. (PEPSR) (SIL15-1999)

space (1) (data transmission) One of the two possible conti-tions of an element (bit); an open line in a neutral circuit. Is tions of an element (bit); an open line in a nestral circulation of two unit intervals between actors and six unit intervals between words. (PE) 599-1985w

(C) 610.10-1994v